





Window Cam Handle

PERFORMANCE RANGE

Mid range

TYPICAL TECHNICAL FEATURES

Nominal Wall Thickness	1.30 mm
Standard Frame Depth	40 mm
Maximum Frame/ Mullion Depth	100 mm
Glazing Gap	12 - 28 mm
Multipoint Locking System	Available
Sub-frame	Compatible
Overlapping Inner Frames	Standard

PERFORMANCE TEST

This casement window suite had been tested in compliance to MS 832 : 2011 performance test procedure for:-

1. 1000Pa windload - Passed.
2. 150Pa air leakage - Passed.
3. 150Pa water infiltration - Passed.

Note: Test report available upon request.







PERFORMANCE RANGE

Mid range

TYPICAL TECHNICAL FEATURES

Nominal Wall Thickness	1.20 - 1.60 mm
Standard Frame Depth	40 mm
Maximum Frame/ Mullion Depth	100 mm Depth
Glazing Gap	10 - 33 mm
Multipoint Locking System	Available
Sub-frame	Compatible
Overlapping Inner Frames	Standard
Butt. Hinges	Available (Exposed Only)

PERFORMANCE TEST

This casement window suite had been tested in compliance to MS 832 : 2011 performance test procedure for:-

1. 800Pa windload - Passed.
2. 200Pa air leakage - Passed.
3. 240Pa water infiltration - Passed.

Note: Test report available upon request.

